

July 20, 2017

Mr. Jose Raúl Galindo Flores

LUBRICANTES DE AMERICA S.A. DE C.V.
CARRETERA A GARCIA KM 1.2 INT. 8
PARQUE INDUSTRIAL GONHER
SANTA CATARINA , N.L.
MEXICO, C.P. 66350.

Dear Mr. Jose,

We have reviewed the fluid properties and examined the 35VQ25 pump test results for Lubra Hidraulico 32, ISO VG32 anti-wear hydraulic fluid.

Lubra Hidraulico 32, ISO VG 32 is a blend of 0.85% wt. Lubrizol 5703 and 0.2% wt. Lubrizol 7749B in 5% wt. ExxonMobil Group I 600N and 93.95 % wt. ExxonMobil Group I 150N base oils.

It is our opinion that Lubra Hidraulico 32, ISO VG32 meets the requirements of Eaton E-FDGN-TB002-E specification for hydraulic fluids, recommended for Eaton products and brochure 03-401-2010 Rev 1.

Sincerely



Aaron D. Clark

Aaron D. Clark, M.S.

Manager Material Science COE
Senior Chemist
Hydraulics Group

Copy to

Eaton : Earl Daugherty, Anjeeve George

Lubrizol : Shubhamita Basu