

SAFETY DATA SHEET FOR CHEMICALS

LUBRA GREASE LITHIUM COMPLEX MOLY EP NLGI 3

MSDS: LASA-074.

ULTIMA REVISIÓN: Diciembre 2016

COMPANY INFORMATION

SUSTITUYE: SEPTIEMBRE 2015

Manufacturer	Lubricantes de América, S.A. de C.V.
Emergency Phone	(52) 81 81 22 74 00
Address	Carretera a García Km 1.2 Int. 8, Santa Catarina, N.L. C.P. 66350

I.- PRODUCT IDENTIFICATION

Product Name	LUBRA GREASE LITHIUM COMPLEX MOLY EP NLGI 3
Chemical Name:	LITHIUM BASED GREASE FROM PETROLEUM
Chemical Family	HYDROCARBON
Molecular Formula	LITHIUM SOAP + HYDROCARBON + ADDITIVE
Synonyms	LITHIUM LUBRICANT GREASE

II.- IDENTIFICATION OF DANGER OR DANGERS

DANGER RANGE	HEALTH	FIRE	REACT	SPECIAL
STPS	1	1	0	-
NFPA	1	1	0	-
HMIS	1	1	0	-

PRODUCT LISTED IN NOM-052-SEMARNAT-2005 YES _____ NO X



01 800 838 3200
venta@lubral.com
www.lubral.com



ISO: 9001:2008 Certificate No. 43698
ISO: 14001:2004 Certificate No. 46416
ISO TS: 16949:2009 Certificate No. 55073

ACEITES Y GRASAS
LUBRAL
LUBRICANTES

SAFETY DATA SHEET FOR CHEMICALS

LUBRA GREASE LITHIUM COMPLEX MOLY EP NLGI 3



Palabra de advertencia:

Atención

Indicaciones de peligro:

H319: Provoca irritación ocular grave.
H402: Nocivo para los organismos acuáticos.
H412: Nocivo para los organismos acuáticos, con efectos nocivos duraderos

Consejos de prudencia (prevención):

P280: Llevar guantes/prendas/gafas/máscara de protección.
P273: Evitar su liberación al medio ambiente.
P264: Lavarse con agua y jabón concienzudamente tras la manipulación.

Declaraciones de precaución (respuesta):

P305 + P351 + P338: EN CASO DE CONTACTO CON LOS OJOS: Enjuagar cuidadosamente con agua durante varios minutos. Quitar las lentes de contacto, si lleva y resulta fácil. Seguir enjuagando.

P337 + P311: Si persiste la irritación ocular: Llamar a un

CENTRO DE TOXICOLOGÍA/médico.

Declaraciones de precaución(eliminación):

P501: Eliminar el contenido/el recipiente en un punto de recogida de residuos especiales.

SAFETY DATA SHEET FOR CHEMICALS

LUBRA GREASE LITHIUM COMPLEX MOLY EP NLGI 3

III.- COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name:	CAS NO.	WT %	Exposure Limits-ref STPS-CPT OSHA-PEL ACGIH-TLV
12-Hydrogenated Stearic Acid	106-14-9	Minor 10	TLV 5 mg / m ³
Metal hydroxide	554-13-2	Minor 4	TLV 5 mg / m ³
Oil derived from Petroleum	64742-65-0	Minor 30	TLV 10 mg/m ³
Oil derived from Petroleum	Mixture	Minor 48	TLV 10 mg/m ³
Anti-rust, extreme pressure	Mixture	Minor 6	TLV 10 mg / m ³
Additive Antifriction (powder)	Mixture	Minor 3	TLV 5 mg / m ³

IV.- FIRST AID

FIRST AID PROCEDURES:

INHALATION: Remove victim from source of exposure. Get medical attention if irritation persists.

EYES: Immediately flush with large amounts of water for 15 minutes, you should keep the lids sections of the eyeball to ensure thorough rinsing.

SKIN: Immediately remove contaminated clothing and wash thoroughly the contact area with soap and water.

INGESTION: Do not induce vomiting. If vomiting occurs, watch for spontaneous breathing difficulty and get medical attention.

SPECIAL PRECAUTIONS:

DOCTOR'S MEDICAL DATA FOR : The possible aspiration of mineral oil with high viscosity is very slight, however if aspirated petroleum products may cause severe pneumonitis (oil pneumonia) should consider instituting unwitting victims gastric lavage should be considered the use of an endotracheal tube

SAFETY DATA SHEET FOR CHEMICALS

LUBRA GREASE LITHIUM COMPLEX MOLY EP NLGI 3

V.- FIRE FIGHTING MEASURES

Flash Point (test method ASTM D-92)	N.D.
Flammable or Explosive Limits	N.A.
Lower	N.A.
Upper	N.A.
EXTINGUISHING MEDIA	
Dry Chemical Powder	X
CO ₂	X
FOAM	X
Water Fog	X
Other	

FIRE FIGHTING PROCEDURE

Use water spray to cool containers and structures exposed to fire to protect personnel. Use water to remove spills away from sources of ignition. No drag sewers or other drainage system.

PERSONAL PROTECTION EQUIPMENT

Use Regular-out gear with SCBA.
(Self-Contained Breathing Apparatus)

SPECIAL RISKS AND HARMFUL COMBUSTION PRODUCTS

Combustible at elevated temperatures. During the thermal decomposition may be released irritating or toxic substances. Exposed firefighters must wear masks and protective equipment.

NOTE: N.A. - Not applied N.D. - Not Determined N.E. - Not established

VI.- MEASURES TO TAKE IN CASE OF ACCIDENTAL SPILL

GENERAL: Stop leak if possible without risk.

SMALL LEAK: Take up with sand or other noncombustible absorbent material and place in containers for disposal later.

LARGE SPILL: Construct a dike ahead of liquid spill for later disposal.

DISPOSAL METHOD: This material when discarded or disposed of is not specifically included as a hazardous waste in federal regulations, however, may be characteristically hazardous if it is considered corrosive toxic flammable or reactive according to Federal definitions. This substance can also become dangerous if mixed or contact with hazardous waste.

VII.- HANDLING AND STORAGE

PRECAUTIONS: Avoid extremes of temperature during storage

HANDLING: With stowed on pallets and forklifts impo to drum.

STORAGE: in a cool, well ventilated sealed containers, keep it in well ventilated areas and away from heat ignition sources and incompatible materials, do not store in unlabeled containers, not eat, drink or smoke in their storage areas.

01 800 838 3200
venta@lubral.com
www.lubral.com



ISO: 9001:2008 Certificate No. 43698
ISO: 14001:2004 Certificate No. 46416
ISO TS: 16949:2009 Certificate No. 55073



SAFETY DATA SHEET FOR CHEMICALS

LUBRA GREASE LITHIUM COMPLEX MOLY EP NLGI 3

VIII.- EXPOSURE CONTROL /PERSONAL PROTECTION

VENTILATION: Open

BREATHING: If you feel irritation respiratory protection must be used by NIOSH (gas masks) approved.

EYES: Wear safety glasses or goggles and provide an eyewash station in work area. Do not use contact lenses when working with this substance.

GLOVES AND CLOTHING: Wear appropriate protective gloves to chemical agents.

OTHER PROTECTIVE EQUIPMENT: Face masks, apron cover arms, etc.

IX.- PHYSICAL AND CHEMICAL PROPERTIES

Form	Semi-solid
Color	Grey
Odor	hydrocarbon
Molecular weight	N.D.
pH	N.D.
Viscosity:	solid or semisolid
Boiling point	375°C

Melting point:	N.A.
Relative density (water=1)	0.91 – 1.0
Water Solubility	N.A.
Vapor Density (air=1)	Heavy
Vapor Pressure (mm Hg):	N.A.
Evaporation Rate	N.A.
Volatiles, vol %:	N.A.

NOTE: N.A. - Not applied N.D. - Not Determined N.E. - Not established

X.- STABILITY AND REACTIVITY

Stability	Stable
Conditions to avoid	Contact with strong oxidizers
Hazardous Polymerization	N.A.
Incompatible materials	Oxidizer Materials
Hazardous decomposition products	Combustion may produce CO, CO2 and hydrocarbon reactant.

SAFETY DATA SHEET FOR CHEMICALS

LUBRA GREASE LITHIUM COMPLEX MOLY EP NLGI 3

XI.- TOXICOLOGICAL INFORMATION

PRIMARY EXPOSURE ROUTES:

EFFECTS OF ACUTE EXPOSURE: May be irritating to skin, eyes and respiratory tract.

INHALATION: May cause irritation of the respiratory tract, exposure to high concentrations in dense fog can cause pneumonia by oil.

EYES: Slightly irritating. Contact with hot material may cause thermal burns.

SKIN: Slightly irritating repeated or prolonged contact may cause fat loss, acne, redness, itching, swelling, cracking and possible secondary infections.

INGESTION: May cause gastrointestinal disorders, Symptoms may include irritation nausea, vomiting and diarrhea.

EFFECTS OF CHRONIC EXPOSURE: Causes nausea, dizziness and vomiting.

LD50 (oral)	Practically non-toxic
LD50 (dermal)	Practically non-toxic
LC50 (inhalation)	Practically non-toxic
IRRITATING DOSE EYES	Not irritating
DOSE IRRITATING SKIN	Not irritating
EYE IRRITANT	Not irritating
SKIN IRRITATION	Not irritating
SKIN SENSITIZATION	Not sensitizing

XII.- ECOTOXICOLOGICAL INFORMATION

Ecotoxicity

Not regarded as dangerous for the environment.

Mobility in soil

Toxicity

Persistence and degradability

Degradability

There are no data on the degradability of this product.

Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

>3.5

Mobility:

The product contains substances, which are insoluble in water and which may spread on water surfaces.

Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

Other adverse effects

Not available.

SAFETY DATA SHEET FOR CHEMICALS

LUBRA GREASE LITHIUM COMPLEX MOLY EP NLGI 3

XIII.- INFORMATION REGARDING THE DISPOSAL OF PRODUCTS

Concerning the package:

The method of disposal of packaging will be provided by the user in accordance with applicable laws and regulations, according to the product characteristics.

Product listing on NOM-052-SEMARNAT-2005

Yes No

Concerning the content

The contents of the package must be disposed of according to local, state or federal regulations, as applicable.

XIV.-RELATIVE TRANSPORT INFORMATION

Appropriate transportation Name	Lubricant Grease
ID NUMBER (ONU)	N.D.
HAZARD CLASS	N.A.
Response guide No DOT	N.A.

XV.- REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Statutory Instruments

It covers the NOM-028-STPS-2012 and NOM-056-SSA1-2012.

01 800 838 3200
venta@lubral.com
www.lubral.com



ISO: 9001:2008 Certificate No. 43698
ISO: 14001:2004 Certificate No. 46416
ISO TS: 16949:2009 Certificate No. 55073



SAFETY DATA SHEET FOR CHEMICALS

LUBRA GREASE LITHIUM COMPLEX MOLY EP NLGI 3

XVI.- OTHER INFORMATION

Information related to this product may not be valid if it is used in combination with other materials or in other processes.

Users are responsible for the interpretation and application of this information for their own use.

CAS	Chemical Abstract Services	DL50	Median Lethal Dose
Lim. Exp.	Exposure Limit	ONU	United Nations
°C	Degree Celcius	DOT	USA (Departament of Tranportation)
N/A	Not Applicable	pH	Potential Hydrogen
N/D	Not Availalble	% Vol.	Volume percent (Vol %)
NIOSH	National Institute for Occupational Safety and Healthy	mg/m3	Milligrams per cubic meter, Concentration unit.
cSt	Centistokes	mmHg	Millimeters of Mercury
CL50	Lethal Concentration Average		

