

LUBRA FLUID TRACTOR WB

MULTI-PURPOSE HYDRAULIC FLUID

DESCRIPTION

LUBRA FLUID TRACTOR WB is a superior multi-purpose tractor hydraulic fluid recommended for Ford/New Holland Tractors with combined transmission, differential, wet brakes, hydraulic and hydrostatic systems. This product is a special blend of selected high quality paraffinic base oil, high performance additives system, and a shear stable viscosity index improver.

This fluid is designed to prevent wear in the heavily loaded transmission and differential gear assembly. It also provides the high viscosity performance required by today's tractors to handle demanding field conditions. This product meets Ford/New Holland Specifications.

FEATURES AND BENEFITS

- Low operating costs: LUBRAFLUID TRACTOR WB meets or exceeds fluid performance requirements of most OEM's, maintaining efficiency and reliability while minimizing overall operating costs.
- Long equipment life: Special additives protect metal surfaces against scuffing and wear even under severe operating conditions leading to maximum equipment life.

- Minimizing weather and storage concerns: Protects against rust and corrosion of highly finished precision parts when operating in humid conditions and during seasonal shutdown periods.
- Smooth operation: Formulated to suppress brake "chatter" and transmission "slip" for quiet and efficient action of brakes and transmission.
- Reliable operation: Formulation helps keep metal parts clean and free of varnish and sludge deposits that could result in premature breakdown.

Also LUBRA FLUID TRACTOR WB is a high quality, multifunctional tractor hydraulic fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir.

It is formulated with highly refined base stocks, a viscosity index improver, oxidation and corrosion inhibitors, antiwear and film strength additives, an antifoaming agent, and a pour point depressant.



LUBRA FLUID TRACTOR WB

MULTI-PURPOSE HYDRAULIC FLUID

APPLICATIONS

LUBRA FLUID TRACTOR WB meets the needs of modern tractors for a multi-functional lubricant. It is designed for many uses, such as lubrication of the transmission and final drive, and serves as a hydraulic fluid to operate power steering units, brakes, implements, and attachments.

LUBRA FLUID TRACTOR WB is formulated to suppress brake “chatter” and excessive brake facing wear. It offers smooth operation of clutch packs and wet brakes, provides excellent shifting action, provides exceptional rust and corrosion protection for vital parts, and minimizes leakage because of good compatibility with seals, O-rings, and packing materials.

It helps prevent sludge and varnish formation, protects metal surfaces against scuffing and wear, and provides outstanding lubrication for spur, helical, and spiral bevel final drive gears, also the oil covers the GL-4 API specification.

LUBRA FLUID TRACTOR WB is compatible with equipment manufacturer’s proprietary fluids and other fluids of this type.

Also LUBRA FLUID TRACTOR WB IS RECOMMENDED TO:

- As a multifunctional fluid in many types of farm tractors and equipment.
- In applications which call for the following OEM lubricant specifications:

Case New Holland — MAT 3525 (134-D)

Ford New Holland — ESN-M2C86-B

Massey Ferguson — M1135

01 800 838 3200
venta@lubral.com
www.lubral.com



ISO: 9001:2008 Certificate No. 43698
ISO: 14001:2004 Certificate No. 46416
ISO TS: 16949:2009 Certificate No. 55073



LUBRA FLUID TRACTOR WB

MULTI-PURPOSE HYDRAULIC FLUID

TYPICAL PROPERTIES

PROPERTIES	ASTM METHOD	
Appearance	Visual	Clear & Brilliant
API Gravity	D1298	To report
Flash Point, COC, °C	D92	220
Pour point, °C	D97	-39
Kinematic Viscosity @ 40 °C, cSt	D445	To Report
Kinematic Viscosity @ 100 °C, cSt	D445	9.5
Viscosity Index	D2270	138

Typical Properties are those obtained with normal production tolerance and do not constitute a specification. Variations that not affect product performance are expected during normal manufacture and at different mixing process. The information contained in this document is subject to change without notice. The availability of the products may vary depending on the locality. For more information, contact us at venta@lubral.com

01 800 838 3200
venta@lubral.com
www.lubral.com



ISO: 9001:2008 Certificate No. 43698
ISO: 14001:2004 Certificate No. 46416
ISO TS: 16949:2009 Certificate No. 55073

