

LUBRAL ANTIFREEZE

CONCENTRATE

DESCRIPTION

LUBRAL ANTIFREEZE CONCENTRATE is a formulation based on Ethylene Glycol with performance characteristics suitable for cooling systems of combustion machines that are made of metals or alloys of the type Aluminum, Steel, Copper, Iron and Bronze.

In its formulation the antifreeze contains anti-corrosive additives, anti-rust and metal passivators that protect against rust and corrosion of the cooling systems, preventing leakage in the radiator and damage to the water pump and thermostat.

FEATURES AND BENEFITS:

- Maximum protection at low and high temperatures.
- Maximum protection against rust and corrosion.
- Good protection in long periods of change.
- Excellent protection in Aluminum, Steel, Copper, Brass, Iron, Hoses, Rubber and Seals.
- Meets or exceeds SAE J-1034 and ASTM D3306 specifications for Ethylene glycol base machine antifreeze.

APPLICATIONS

Meets SAE J1034 and ASTM D3306 specifications for ethylene glycol base machine anti-freeze, recommended for most domestic and imported automotive vehicles, passenger cars, light duty trucks, TMC RP-329 y US/NATO MILITARY CID A-A-52624.



LUBRAL ANTIFREEZE

CONCENTRATET

TYPICAL PROPERTIES

PROPERTIES	ASTM METHOD	
Density @ (20°C), g/ml	D1122	1.10
Base		Ethylene Glycol
Freezing point undiluted, °C	D1177	-50
Boiling Point undiluted, °C	D1120	116
pH, undiluted solution	D1287	10
Color	Visual	Fluorescent Yellow
Water Content, % w	D1123	30
Reserve Alkalinity	D1121	Report

Typical Properties are those obtained with normal production tolerance and do not constitute a specification. Variations that not affect product performance are expected during normal manufacture and at different mixing process. The information contained in this document is subject to change without notice. The availability of the products may vary depending on the locality. For more information, contact us at venta@lubral.com

